



P2788-06, P2788-08, P2788-10, P2788-12



Part No.	Beam Flange Width	Beam Load
P2788-06	4" - 6"	1500 lbs.
P2788-08	6 1/8" - 8"	1500 lbs.
P2788-10	8 1/8" - 10"	1500 lbs.
P2788-12	10 1/8" - 12"	1500 lbs.

Specifications:

- Beam Flange width ranging from 4"-12"
- Compatible with any 1-5/8" strut profile
- Serrated inside face to prevent slippage
- Beam Flange thickness up to 7/8"
- Slopes up to 18°

NOTE: patent pending

I-beam, Channel, Hex Head Cap Screws and Channel Nut not included

Standard Dimensions for 1 5/8" (41mm) width series channel fittings *(Unless Otherwise Shown on Drawing)*

Hole Diameter: 5/16" (14mm); Hole Spacing - From End: 13/16" (21mm); Hole Spacing - On Center: 1 1/8" (48mm); Width: 1 5/8" (41mm); Thickness: 1/4" (6mm)

Note: When used for mechanical supports, load capacities of brackets and fittings should be in compliance with the American Standard Code for Pressure Piping. Clamps are designed to be used with W, M, S & HP Shape beams, Standard C & Misc. MC Channels, Angles & Structural Tees. Clamps must be used in pairs where indicated. For beam clamps with HG finish, standard hardware is EG finish. For optional stainless steel hardware, please contact the factory for availability.

MATERIAL

Fittings, unless noted, are made from hot-rolled, pickled and oiled steel plates, strip or coil, and conform to ASTM specifications A575, A576, A635, or A36. The fitting steel also meets the physical requirements of ASTM A1011 SS GR 33. The pickling of the steel produces a smooth surface free from scale.

Many fittings are also available in stainless steel, aluminum and fiberglass. Consult factory for ordering information.

FINISHES

Fittings available in:

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1;

Project: _____ Architect / Engineer: _____ Date: _____ Phone: _____ Contractor: _____ Address: _____ _____ Notes 1: _____ _____ Notes 2: _____ _____	Approval Stamp:
---	--